MITSUBISHI FUSO



Beyond Compare



FUSO TRUCK TRACTOR-FV517JR2RDR1

SPECIFICATIONS*

96 km / hr. Max. Speed Max. Gradeability

MITSUBISHI 6D24-0AT2 Model

Туре 4 stroke-cycle, 6 cylinder, water cooled, direct injection,

turbocharged with intercooler diesel engine

Piston Displacement 11,945 cc

Bore x Stroke

Max. Output 360 PS (250 kW) @ 2,200 rpm Max. Torque 142 Kgfm (1,395 N.m) @ 1,400 rpm

Hydraulic control, coil spring type, single dry plate with air Type

pressure assistance

Size

10 Forward and 2 Reverse Speed Overdrive transmission with air operated shift cylinder for splitter

Speed	Gear Type	Transmission Ratio	Final Reduction Ratio
1st Low / High	Constantmesh	9.153 / 7.005	56.437 / 43.193
2nd Low / High	Synchromesh	5.444 / 4.166	33.568 / 25.667
3rd Low / High	Synchromesh	3.080 / 2.357	18.991 / 14.533
4th Low / High	Synchromesh	1.762 / 1.349	10.864 / 08.318
5th Low / High	Synchromesh	1.000 / 0.765	06.166 / 04.717
Reverse Low / High	Constantmesh	7.929 / 6.068	48.890 / 37.415
Final Gear Ratio		6.166	

Front

Axle Capacity 7,500 kg

Full floating type, tandem drive with inter-axle differential gear and locking device Rear

Axle Capacity 21,600 kg

Full Air, dual circuit, wedge type. Equipped with ABS Spring loaded type on 1st & 2nd rear wheels by hand control valve Service Parking & Emergency

Exhaust Brake and Powertard

Auxiliary Type

Power Steering. Ball nut type with integral type hydraulic power


booster. Telescopic and tilt steering column with steering lock.

11.00-20-16PR Size

No. of Studs

FUEL TANK Capacity	400 Liters	
ELECTRICAL SYSTEM		
Battery Generator	12 Volt x 2, 170 AH 24 Volt, 50 Amp	
WEIGHT		
Max. GCW Kerb Weight Front Rear	kg kg kg kg	60,000 7,795 4,030 3,765

Wheelbase	mm	4,520
Overall Length	mm	6,690
Overall Width	mm	2,490
Overall Height (Approx.)	mm	2,890
Tread Front	mm	2,050
Tread Rear	mm	1,850



All steel, Coil Spring Suspension Cab, tilted by Hydraulic Cylinder